

# VX-160E Series

## VHF/UHF Portable Radio

### SPECIFICATION SHEET

## Industrial Grade Radio For Every Day Communications

The VX-160E is designed with a die-cast chassis that provides a solid, rugged foundation to survive real-world industrial use. Includes the fundamental features needed for users to keep in contact while remaining focused on the job at hand.

### Paging and DTMF ANI Built-In

The VX-160E provides dual 2-tone decode that can be used for two individual pager calls or for a combination of Individual and Group calling. It also includes DTMF ANI that will respond to an incoming ANI burst for selective paging of an individual portable.

### High-Speed Scanning Capability

Get unmatched flexibility in scanning features for the price. In addition to basic scan, you also get Priority, Dual Watch and Follow-me scan included.

### Solid Audio Output

Designed with 500 mW audio output makes the VX-160E ideal for noisy environments. The high-powered audio is coupled with a large internal speaker, assuring loud and clear audio.

### Maximise Battery Life

The VX-160E includes RX/TX (receive and transmit) battery saver capability. During receive, the radio will put itself into saver mode while periodically checking for channel activity. During transmit, the VX-160E will automatically reduce power when the incoming signal is very strong.

### Exclusive Auto-Range Transpond System – ARTS™

Only Vertex Standard radios are designed to inform you when you and another ARTS™-equipped station are within communication range. If out of range for more than 2 minutes, your radio senses no signal has been received and beeps to alert you. The base station can then alert the field unit to move back in range. A great solution to keep your workers co-ordinated.

### The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Count on Vertex Standard for radios that are built to last and designed to provide more features for a better return on your investment. Ask your Dealer for more details.



## Additional Features

- 16 channel capacity
- CTCSS / DCS Encode and Decode
- BCLO
- BTLO
- TOT
- Radio-to-radio cloning

## Accessories

- MH-45B4B: Noise cancelling speaker microphone
- MH-450S: Speaker microphone
- MH-360S: Compact speaker microphone
- MH-37A4B: Earpiece microphone
- VH-110S: Over-the-head headset
- VH-120S: 3-Wire earpiece mic w/palm PTT switch
- VH-130S: 2-Wire earpiece w/palm mic and PTT switch
- VH-115S: Behind-the-head headset w/boom mic
- VH-215S: Over-the-head single-muff headset
- VC-25: Over-the-head VOX headset
- FNB-V67LI: 2000 mAh Li-Ion battery
- FNB-V94: 1800 mAh Ni-MH battery
- FNB-83: 1400 mAh Ni-MH battery
- FNB-57: 1100 mAh Ni-Cd battery
- VAC-6810: 6-Unit multi rapid charger (FNB-67LI)
- VAC-6010: 6-Unit charger (FNB-83, FNB-V94)
- VAC-810: Desktop rapid charger (FNB-67LI)
- VAC-10: Desktop charger (FNB-83, FNB-V94)
- DCM-1: Desktop charger mounting adapter
- VCM-3: Vehicle mounting adapter for VAC-10
- VCM-1: Vehicle mounting adapter for VAC-800/810
- FBA-25A: Alkaline battery case (holds 6 AA batteries)
- LCC-160: Leather case
- LCC-160S: Leather case w/swivel belt clip
- CLIP-17C: Swivel belt clip

## VX-160E Series Specifications



	VHF	UHF
<b>General Specification</b>		
Frequency Range	134 – 160 MHz (A) 142 – 176 MHz (C)	400 – 430 MHz (AS1) 440 – 470 MHz (CS)
Number of Channels	16	
Power Supply Voltage	7.5V DC ± 20%	
Channel Spacing	12.5/20/25 kHz	
PLL Steps	2.5 / 6.25 kHz	5 / 6.25 kHz
Battery Life (5-5-90 duty) 2000 mAh FNB-V67LI	18 hours (14.8 hrs w/o saver)	12.3 hours (10.3 hrs w/o saver)
IP Rating	IP 54	
Operating Temperature Range	-20° C to +55° C	
Frequency Stability	±2.5 ppm, ± 1.5 kHz	
RF Input-Output Impedance	50 Ohms	
Dimension (H x W x D)	120 x 58 x 31 mm (w/FNB-67LI)	
Weight (Approx.)	320g (w/FNB-67LI, Antenna, Belt Clip)	
<b>Receiver Specification</b> measured by EN 300 086		
Sensitivity EN 20dB SINAD	-3 dB µV emf	
Adjacent Channel Selectivity	65 dB	
Intermodulation	65 dB	
Spurious and Image Rejection	70 dB	
Audio Output	500mW @ 4 Ohms 10% THD	
<b>Transmitter Specification</b> measured by EN 300 086		
Output Power	5 / 1 W	
Modulation	16K0F3E, 14K0F3E, 11K0F3E	
Conducted Spurious Emissions	70 dB below carrier -36 dBm @ ≤ 1 GHz; -30 dBm @ > 1 GHz	
Audio Distortion	< 5 % @ 1kHz	

## Applicable MIL-STD

Standard	MIL 810C Methods/ Procedures	MIL 810D Methods/ Procedures	MIL 810E Methods/ Procedures
Low Pressure	-	500.2/Procedure I	500.3/Procedure I
High Temperature	-	501.2/Procedure I, II	501.3/Procedure I, II
Low Temperature	-	502.2/Procedure I, II	502.3/Procedure I, II
Temperature Shock	-	503.2/Procedure I	503.3/Procedure I
Solar Radiation	-	505.2/Procedure I	505.2/Procedure I
Rain	-	506.2/Procedure II	506.3/Procedure II
Humidity	-	507.2/Procedure II	507.3/Procedure II
Salt Fog	-	509.2/Procedure I	509.3/Procedure I
Dust	-	510.2/Procedure I	510.3/Procedure I
Vibration	514.2/Procedure VIII	514.3/Procedure I Cat. 10	514.4/Procedure I Cat. 10
Shock	516.2/Procedure I	516.3/Procedure I, IV	516.4/Procedure I, IV

Specifications are subject to change without notice or obligation.

VERTEX STANDARD is registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. CESS160\_4/2009